



PVC SDR 26 D3034 SEWER PIPE  
GASKET JOINT

CNWPVC-263034GJ

JANUARY, 2016

20' GASKET JOINT PSM SEWER PIPE SDR-26 ASTM D3034 GREEN	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	PART NO.
	4"	4.215	3.891	.162	145.38	1200	6.6	53507
	6	6.275	5.793	.241	322.45	660	8.4	53527
	8	8.400	7.754	.323	581.50	400	8.9	53529
	10	10.500	9.692	.404	909.26	160	5.6	53530
	12	12.500	11.538	.481	1290.43	160	9.5	53540

20' LAYING LENGTHS. INSERTION DEPTH RING IS MARKED ON THE BEVELED SPIGOT END OF PIPE.

GASKET JOINT PIPE IS PRODUCED WITH AN INTEGRAL BELL END WITH A REINFORCED GASKET CONFORMING TO ASTM F477.

REFER TO ASTM D2321 FOR PROPER INSTALLATION PROCEDURES OF SDR-26 SEWER PIPE.

CRESLINE – NORTHWEST, LLC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300

PLANT: 223 MAURIN ROAD • CHEHALIS, WA 98532 • TELEPHONE (360) 740-0708 • FAX (360) 740-0721

www.cresline.com