



**PVC-DWV
CELLULAR CORE
PERFORATED**

CNWPVC-DWVCCPERF

JANUARY, 2016

20' BELLED END PERFORATED PVC-DWV CELLULAR CORE DRAIN, WASTE & VENT ASTM F891	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PERCENT OF TL	MIN. BELL LENGTH	PART NO. PERF.
	3"	3.500	3.068	.216	94.25	1500	5.0	4.0	51138
	4	4.500	4.026	.237	134.17	960	5.0	4.0	51150
	6	6.625	6.065	.280	236.39	400	5.6	6.0	51158

PERFORATED WITH 2 ROWS OF 5/8" HOLES ON 5" CENTERS 120° APART.

THE ADVANTAGES OF CELLULAR CORE

- LIGHTER WEIGHT
 - EXCELLENT TENSILE STRENGTH
 - LOWER WASTE NOISE
 - CARRIES NSF-DWV LISTING
 - ASTM F891
- HIGH STIFFNESS AND IMPACT STRENGTH
 - EASIER TO CUT AND SAW
 - SCHEDULE 40
 - LOWER COST

NOTE: USES THE SAME FITTINGS, PVC CEMENT AND INSTALLATION PROCEDURES AS CONVENTIONAL PVC-DWV PIPE

CRESLINE – NORTHWEST, LLC.
 CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300
 PLANT: 223 MAURIN ROAD • CHEHALIS, WA 98532 • TELEPHONE (360) 740-0708 • FAX (360) 740-0721