




<b>SDR-26</b> PRESSURE PIPE 160 PSI PVC1120 ASTM D2241 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	BELLED PART NO.
	1¼"	1.660	1.532	.064	20.93	4000	32	45243
	1½	1.900	1.754	.073	27.31	3600	28	45280
	2	2.375	2.193	.091	42.51	2800	24	45345
	2½	2.875	2.655	.110	62.13	2240	20	45410
	3	3.500	3.230	.135	92.81	1500	20	45470
	4*	4.500	4.154	.173	158.24	580	28	47075
	6*	6.625	6.115	.255	343.40	400	20	47120
	8	8.625	7.961	.332	554.30	280	16	45695

NOTE: 8" SDR-26 IS DUAL MARKED FOR SCH-40 PIPE.

<b>SDR-21</b> PRESSURE PIPE 200 PSI PVC1120 ASTM D2241 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	BELLED PART NO.
	¾"	1.050	.930	.060	12.11	6600	40	46157
	1	1.315	1.189	.063	16.17	5400	32	46207
	1¼	1.660	1.502	.079	25.59	4000	32	46243
	1½	1.900	1.720	.090	33.32	3600	28	46285
	2	2.375	2.149	.113	52.32	2800	24	46345
	2½	2.875	2.601	.137	76.53	2240	20	46410
	3	3.500	3.166	.167	113.71	1500	20	46470
	4*	4.500	4.072	.214	192.22	580	28	47275
	5*	5.563	5.033	.265	296.52	460	24	47307
	6*	6.625	5.993	.316	420.11	400	20	47320
	8*	8.625	7.805	.410	710.96	280	16	47335
	10*	10.750	9.728	.511	1108.90	160	16	47355
12*	12.750	11.538	.606	1563.60	120	12	47375	

\*PIPE DUAL MARKED FOR POTABLE WATER AND WELL CASING (20' LAYING LENGTHS).

<b>SDR-13.5</b> PRESSURE PIPE 315 PSI PVC1120 ASTM D2241 	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	BELLED PART NO.
	½"	.840	.716	.062	9.81	8400	44	46105
	2	2.375	2.023	.176	78.80	2800	24	46025
	2½	2.875	2.449	.213	113.50	2240	20	46035
	3	3.500	2.982	.259	170.70	1500	20	46045
4	4.500	3.834	.333	281.80	580	28	46055	

NOT RECOMMENDED FOR THREADING.

ALL SDR-26, SDR-21, AND SDR-13.5 PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

ALL SDR-26, SDR-21, AND SDR-13.5 PIPE IS CERTIFIED TO NSF/ANSI 61, ANNEX G (CA AND VT LEAD FREE LAWS) BY NSF INTERNATIONAL.

CERTIFIED TO NSF/ANSI 372 (LEAD FREE LAWS).

**PRESSURE RATINGS  
FOR CRESLINE - PVC PIPE  
AT 73.4° F**

SIZE	½	¾	1	1¼	1½	2	2½	3	4	5	6	8	10	12
SDR-26	--	--	--	160	160	160	160	160	160	--	160	160	--	--
SDR-21	--	200	200	200	200	200	200	200	200	200	200	200	200	200
SDR-13.5	315	--	--	--	--	315	315	315	315	--	--	--	--	--

**CONVERSION CHART FOR PRESSURE RATINGS  
AT VARIOUS TEMPERATURES FOR CRESLINE - PVC PIPE**

TEMPERATURE °F	73.4°	80°	90°	100°	110°	120°	130°	140°
CONVERSION FACTOR	1.00	.88	.75	.62	.50	.40	.30	.22

PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.

**DO NOT USE PLASTIC PIPE AND FITTINGS FOR COMPRESSED AIR.**

**PALLET QUANTITIES PVC PRESSURE PIPE**

PIPE SIZE	FEET PER PALLET	WT. PER PALLET		
		SDR-26	SDR-21	SDR-13.5
½"	8400	--	--	824
¾	6600	--	800	--
1	5400	--	874	--
1¼	4000	837	1024	--
1½	3600	983	1200	--
2	2800	1190	1465	2206
2½	2240	1392	1715	2542
3	1500	1393	1706	2561
4	580	918	1115	1635
5	460	--	1364	--
6	400	1374	1680	--
8	280	1552	1991	--
10	160	--	1774	--
12	120	--	1876	--

**PVC SDR-26, SDR-21, AND SDR13.5 CAN BE USED ON  
JET OR SUBMERSIBLE PUMPS OF 1 HP OR LESS**

MAXIMUM DEPTH SETTING TO WATER LEVEL IN FT @ 73.4° F			
CRESLINE PVC PRESSURE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
ANY SIZE PVC SDR-26	275'	255'	230'
ANY SIZE PVC SDR-21	365'	345'	320'
ANY SIZE PVC SDR-13.5	635'	610'	585'



**NSF® pw-G U.P. Code**

**CRESLINE - WEST, INC.**

**CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD • EVANSVILLE, IN 47715 • TELEPHONE (812) 428-9300  
PLANT: 3747 W. BUCKEYE ROAD • PHOENIX, AZ 85009 • TELEPHONE (602) 269-5161  
WAREHOUSE: 1930 W. WHITESBRIDGE ROAD • FRESNO, CA 93706 • TELEPHONE (559) 486-1840**