

FORM NO. 161-CE SPECIFICATIONS  
PRICES ARE LISTED ON FORM MLP-1.  
PLEASE ORDER BY PART NUMBER.



NOVEMBER, 2015

CE BLUE <sup>®</sup> 250 PSI - CTS SDR - 9 AWWA C-901  NSF <sup>pw</sup>  ASTM D2737	SIZE	O.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
	3/4"	.875	.097	10.20	100	19715
500					19720	
1	1.125	.125	16.85	100	19730	
				300	19735	
				500	19738	
1 1/4	1.375	.153	25.22	100	19750	
				300	19755	
1 1/2	1.625	.181	35.28	100	19770	
				300	19775	
2	2.125	.236	60.23	100	19785	
				200	19790	

CE BLUE <sup>®</sup> 250 PSI - IPS SIDR - 7 AWWA C-901  NSF <sup>pw</sup>  ASTM D2239	SIZE	I.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
	3/4"	.824	.118	15.31	100	19115
400					19120	
1	1.049	.150	24.75	100	19130	
				300	19135	
1 1/4	1.380	.197	42.83	100	19150	
				300	19155	

CE BLUE <sup>®</sup> 200 PSI - IPS SIDR - 9 AWWA C-901  NSF <sup>pw</sup>  ASTM D2239	SIZE	I.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
	3/4"	.824	.092	11.59	100	19315
400					19320	
1	1.049	.117	18.74	100	19330	
				300	19335	
1 1/4	1.380	.153	32.22	100	19350	
				300	19355	

CRESLINE CE BLUE<sup>®</sup> POLYETHYLENE FLEXIBLE PIPE IS PRODUCED FROM HD PE 4710 MATERIAL.

CRESLINE PLASTIC PIPE CO., INC.

[www.cresline.com](http://www.cresline.com)

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732

**PRESSURE RATING  
FOR CRESLINE FLEXIBLE PIPES  
AT VARIOUS TEMPERATURES  
ALL SIZES**

DEGREE °F	73.4° F AND BELOW	100° F	120° F	140° F
<b>CE BLUE® 250</b>	250	200	155	125
<b>CE BLUE® 200</b>	200	155	125	100

**PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.**

**CRESLINE CE BLUE® FLEXIBLE PLASTIC PIPE MAY BE USED ON SUBMERSIBLE PUMPS OF 1.5 HP OR LESS.**

MAXIMUM DEPTH SETTINGS TO WATER LEVEL IN FT @ 60° F			
CRESLINE PE FLEXIBLE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
<b>CE BLUE® 250</b>	530'	510'	485'
<b>CE BLUE® 200</b>	420'	400'	370'



**CRESLINE PLASTIC PIPE CO., INC.**

[www.cresline.com](http://www.cresline.com)

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732